NSN 5325-01-132-0711

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-132-0711

| Cross Sectional Shape: |
|--|
| Rounded corners |
| Inside Diameter: |
| Between 1.505 inches and 1.545 inches |
| Casehardening Indicator: |
| Not casehardened |
| Outside Diameter: |
| Between 1.795 inches and 1.815 inches |
| Major Thickness: |
| Between 0.027 inches and 0.033 inches |
| End Style: |
| 90 degree parallel |
| Ring Style: |
| Internal |
| Usage Design: |
| External |
| Material Hardness Rating: |
| Between 38.0 rockwell c and 44.0 rockwell c |
| Special Features: |
| 5 holes 0.040 in. Min 0.060 in. Maximum dia |
| Material: |
| Steel, mil-s-18729 or steel, qq-s-700 sae 1095 or steel, astm a682 grade 1095 or steel, astm a684 |
| Material: |
| Steel comp 4130 or steel, qq-s-700 sae 1095 or steel, astm a682 grade 1095 or steel, astm a684 |
| Material Specification: |
| Mil-s-18729 military specification 1st material response |
| Surface Treatment: |
| Cadmium and titanium alloy or cadmium and chromate |
| Surface Treatment Specification: |
| Fp-68 fscm 70210 mfr ref 2nd treatment response or mil-c-8837 type 2 class 2 military specification 4th treatment response |
| Surface Treatment: |
| Titanium-cadmium plate, fp-68 fscm 70210 or cadmium plate, mil-c-8837 type 2 class 2 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T252-g |
| Mil-std (military Standard): |

Mil-s-18729 spec.