

View Online at <https://aerobasegroup.com/nsn/5325-01-164-1739>

**Extended Washer Diameter:**

Between 0.552 inches and 0.563 inches

**Grip Length:**

Between 0.910 inches and 0.930 inches

**Securing Device Type:**

Ring

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

0.300 inches

**Turnlock Stud Head Style:**

Stud head

**Material Accommodated Thickness:**

Between 0.851 inches and 0.920 inches

**Drive Type:**

Socket

**Stud Thread Size And Series/type Designator:**

0.250-28 unf

**Width Across Flats:**

Between 0.367 inches and 0.376 inches

**Stud Head Height:**

0.300 inches

**Stud Shank Major Diameter:**

Between 0.3730 inches and 0.3745 inches

**Material:**

Steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-6049 spec.