

View Online at <https://aerobasegroup.com/nsn/5325-01-175-2185>

**Grip Length:**

0.485 inches

**Diameter:**

0.525 inches

**Center To Center Distance Between Mounting Holes:**

Between 0.873 inches and 0.877 inches

**Mounting Style:**

Plain w/mounting hole

**Securing Device Type:**

Ring

**Turnlock Stud Shank Style:**

Stud shank

**Turnlock Stud Head Style:**

Flat countersunk

**Turnlock Receptacle Style:**

Receptacle

**Receptaclelength:**

1.135 inches

**Receptacle Height:**

0.385 inches

**Receptacle Width:**

0.594 inches

**Material Accommodated Thickness:**

Between 0.291 inches and 0.360 inches

**Drive Type:**

Cross recess

**Stud Shank Major Diameter:**

Between 0.373 inches and 0.375 inches

**Turnlock Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Material:**

Steel comp 1010 or steel comp 1030

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Specification Data:**

81349-mil-f-5591 government specification

**Specification Or Standard:**

2 type and b class and 3 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-f-5591 spec.