

View Online at <https://aerobasegroup.com/nsn/5325-01-175-2185>

Grip Length:

0.485 inches

Diameter:

0.525 inches

Center To Center Distance Between Mounting Holes:

Between 0.873 inches and 0.877 inches

Mounting Style:

Plain w/mounting hole

Securing Device Type:

Ring

Turnlock Stud Shank Style:

Stud shank

Turnlock Stud Head Style:

Flat countersunk

Turnlock Receptacle Style:

Receptacle

Receptaclelength:

1.135 inches

Receptacle Height:

0.385 inches

Receptacle Width:

0.594 inches

Material Accommodated Thickness:

Between 0.291 inches and 0.360 inches

Drive Type:

Cross recess

Stud Shank Major Diameter:

Between 0.373 inches and 0.375 inches

Turnlock Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Material:

Steel comp 1010 or steel comp 1030

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Specification Data:

81349-mil-f-5591 government specification

Specification Or Standard:

2 type and b class and 3 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A05400

Mil-std (military Standard):

Mil-f-5591 spec.