

View Online at <https://aerobasegroup.com/nsn/5325-01-184-3855>

Cross Sectional Shape:

Double oval

Inside Diameter:

Between 0.456 inches and 0.469 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

Between 0.538 inches and 0.567 inches

Major Thickness:

Between 0.033 inches and 0.037 inches

Ring Style:

Spiral

Usage Design:

External

Strength Rating:

200000.0 pounds per square inch tensile

Material:

Steel, federal standard 66, comp 302 or steel, mil-s-5059, type 302 or steel, ams 5519 or steel, qq-s-766, class 302

Material:

Steel comp 302 or steel comp 302 or steel comp 301 or steel comp 302

Material Specification:

Fed standard 66, comp 302 federal standard 1st material response and mil-s-5059, type 302 military specification 2nd material response and ams 5519 assn standard 3rd material response and qq-s-766, class 302 federal specification 4th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Surface Treatment:

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-g

Mil-std (military Standard):

Mil-s-5059 spec.