

View Online at <https://aerobasegroup.com/nsn/5325-01-200-2566>

Cross Sectional Shape:

Double oval

Inside Diameter:

Between 1.246 inches and 1.277 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

Between 1.442 inches and 1.457 inches

Major Thickness:

Between 0.041 inches and 0.045 inches

Ring Style:

Special flat

Usage Design:

Internal

Material Hardness Rating:

Between 60.0 rockwell superficial 30-n and 71.0 rockwell superficial 30-n

Material:

Steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1075 or steel, mil-s-46049, comp 1085

Material:

Steel comp 1074 or steel comp 1075 or steel comp 1085

Material Specification:

Mil-s-46049, comp 1074 military specification 1st material response and mil-s-46049, comp 1075 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Dod-p-16232, type z, class 2 def stan/spec single treatment response

Surface Treatment:

Phosphate, dod-p-16232, type z, class 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-g

Mil-std (military Standard):

Mil-s-46049 spec.