

View Online at <https://aerobasegroup.com/nsn/5325-01-217-1021>

**Cross Sectional Shape:**

Rectangular

**Inside Diameter:**

Between 1.301 inches and 1.321 inches

**Casehardening Indicator:**

Not casehardened

**Outside Diameter:**

Between 1.513 inches and 1.545 inches

**Major Thickness:**

Between 0.048 inches and 0.052 inches

**End Style:**

Vertex outside periphery

**Ring Style:**

Straight gap

**Usage Design:**

External

**Material Hardness Rating:**

Between 43.0 rockwell c and 53.0 rockwell c

**Material:**

Steel, sae 1060 or steel, sae 1064 or steel, sae 1065 or steel, sae 1066 or steel, sae 1069 or steel, sae 1070 or steel, sae 1072 or steel, sae 1074 or steel, sae 1075 or steel, sae 1078 or steel, sae 1080 or steel, sae 1084 or steel, sae 1085 or steel, sae 1086 or steel, sae 1090 or steel, sae 1095

**Material:**

Steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel, sae 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp 1080 or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095

**Material Specification:**

Sae 1060 assn standard 1st material response and sae 1064 assn standard 2nd material response and sae 1065 assn standard 3rd material response and sae 1066 assn standard 4th material response and sae 1069 assn standard 5th material response and sae 1072 assn standard 7th material response and sae 1074 assn standard 8th material response and sae 1075 assn standard 9th material response and sae 1078 assn standard 10th material response and sae 1080 assn standard 11th material response and sae 1084 assn standard 12th material response and sae 1085 assn standard 13th material response and sae 1086 assn standard 14th material response and sae 1090 assn standard 15th material response and sae 1095 assn standard 16th material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-g