

View Online at <https://aerobasegroup.com/nsn/5325-01-217-4261>

Cross Sectional Shape:

Rectangular

Inside Diameter:

Between 1.351 inches and 1.388 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

Between 1.607 inches and 1.632 inches

Major Thickness:

Between 0.048 inches and 0.052 inches

Ring Style:

Internal stepped

Usage Design:

Internal

Material Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel, sae 1060 or steel, sae 1064 or steel, sae 1065 or steel, sae 1066 or steel, sae 1069 or steel, sae 1070 or steel, sae 1072 or steel, sae 1074 or steel, sae 1075 or steel, sae 1078 or steel, sae 1080 or steel, sae 1084 or steel, sae 1085 or steel, sae 1086 or steel, sae 1090 or steel, sae 1095

Material:

Steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel, sae 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp 1080 or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095

Material Specification:

Sae 1060 assn standard 1st material response and sae 1064 assn standard 2nd material response and sae 1065 assn standard 3rd material response and sae 1066 assn standard 4th material response and sae 1069 assn standard 5th material response and sae 1072 assn standard 7th material response and sae 1074 assn standard 8th material response and sae 1075 assn standard 9th material response and sae 1078 assn standard 10th material response and sae 1080 assn standard 11th material response and sae 1084 assn standard 12th material response and sae 1085 assn standard 13th material response and sae 1086 assn standard 14th material response and sae 1090 assn standard 15th material response and sae 1095 assn standard 16th material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-g