

View Online at <https://aerobasegroup.com/nsn/5325-01-224-6935>

Cross Sectional Shape:

Double oval

Inside Diameter:

Between 1.516 inches and 1.536 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

Between 1.772 inches and 1.792 inches

Major Thickness:

Between 0.059 inches and 0.065 inches

Ring Style:

Special flat

Usage Design:

Internal

Material Hardness Rating:

Between 40.0 rockwell c and 51.5 rockwell c

Material:

Steel, federal standard 66, comp 1060 or steel, federal standard 66, comp 1061 or steel, federal standard 66, comp 1064 or steel, federal standard 66, comp 1065 or steel, federal standard 66, comp 1066 or steel, federal standard 66, comp 1069 or steel, federal standard 66, comp 1070 or steel, federal standard 66, comp 1072 or steel, federal standard 66, comp 1074 or steel, federal standard 66, comp 1075 or steel, federal standard 66, comp 1078 or steel, federal standard 66, comp 1080 or steel, federal standard 66, comp 1084 or steel, federal standard 66, comp 1085 or steel, federal standard 66, comp 1086 or steel, federal standard 66, comp 1090

Material:

Steel comp 1060 or steel comp 1561 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel, federal standard 66, comp 1069 or steel comp 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp 1080 or steel comp 1070 or steel comp 1085 or steel comp 1086 or steel comp 1090

Material Specification:

Fed standard 66, comp 1060 federal standard 1st material response and federal standard 66, comp 1061 federal standard 2nd material response and federal standard 66, comp 1064 federal standard 3rd material response and federal standard 66, comp 1065 federal standard 4th material response and federal standard 66, comp 1066 federal standard 5th material response and federal standard 66, comp 1070 federal standard 7th material response and federal standard 66, comp 1072 federal standard 8th material response and federal standard 66, comp 1074 federal standard 9th material response and federal standard 66, comp 1075 federal standard 10th material response and federal standard 66, comp 1078 federal standard 11th material response and federal standard 66, comp 1080 federal standard 12th material response and federal standard 66, comp 1084 federal standard 13th material response and federal standard 66, comp 1085 federal standard 14th material response and federal standard 66, comp 1086 federal standard 15th material response and federal standard 66, comp 1090 federal standard 16th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Surface Treatment:

Cadmium, qq-p-416, type 2, class 2

Shelf Life:

N/a

Unit Of Measure: