NSN 5325-01-250-2227

Turnlock Fastener Receptacle - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-250-2227

| view Online at https://aerobasegroup.com/hsn/5325-01-250-2227 |
|---|
| Center To Center Distance Between Mounting Holes: |
| Between 0.686 inches and 0.690 inches |
| Mounting Style: |
| Plain w/mounting hole |
| Turnlock Receptacle Style: |
| Two lug floating |
| Receptaclelength: |
| 0.955 inches |
| Receptacle Height: |
| 0.770 inches |
| Receptacle Width: |
| 0.525 inches |
| Stud Protrusion Length: |
| 0.125 inches |
| Mounting Facility Thread Size And Series/type Designator: |
| 0.164-32 unc |
| Turnlock Mounting Hole Diameter: |
| Between 0.098 inches and 0.103 inches |
| Material: |
| Steel comp 8740 stud |
| Material Specification: |
| Ams6322 assn standard single material response barrel |
| Surface Treatment: |
| Cadmium retainer and chromate retainer |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response retainer |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A05400 |