NSN 5325-01-252-8062

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-252-8062

| Cross Sectional Shape: |
|---|
| Rounded outside corners |
| Inside Diameter: |
| 3.016 inches |
| Casehardening Indicator: |
| Not casehardened |
| Outside Diameter: |
| Between 3.377 inches and 3.407 inches |
| Major Thickness: |
| Between 0.037 inches and 0.041 inches |
| End Style: |
| Vertex center or above |
| Ring Style: |
| Special |
| Usage Design: |
| Internal |
| Strength Rating: |
| 200000.0 pounds per square inch tensile |
| Material: |
| Steel, mil-s-5059, type 302 or steel, qq-s-766, class 302 or steel, ams 5519 or steel, federal standard 66, aisi 302/sae 30302 |
| Material: |
| Steel comp 302 or steel comp 302 or steel comp 301 or steel comp 302 |
| Material Specification: |
| Mil-s-5059, type 302 military specification 1st material response and qq-s-766, class 302 federal specification 2nd material response and |
| ams 5519 assn standard 3rd material response and federal standard 66 federal standard 4th material response or aisi 302 assn standard |
| single material response or sae 30302 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Surface Treatment: |
| Passivated, qq-p-35 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T252-g |
| Mil-std (military Standard): |
| Mil-s-5059 spec. |