## NSN 5325-01-270-4451

Screw Thread Insert - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5325-01-270-4451

Thread Class:         3b         Length:         Between 0.360 inches and 0.390 inches         Insert Size:         0.375-16 unc 2a         Internal Thread Relief Depth:         Between 0.165 inches and 0.185 inches         Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Features Provided:         Individually keyed         Thread Size:         0.250 inches         Special Features:         Dry film lubricated         Surface Treatment:         Passivate         Surface Treatment Specification:         Astm a380 assn standard single treatment response         Style Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:         A03100	
Length:         Between 0.360 inches and 0.390 inches         Insert Size:         0.375-16 unc 2a         Internal Thread Relief Depth:         Between 0.165 inches and 0.185 inches         Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Fatures Provide:         Individually keyed         Thread Size:         0.250 inches         Special Features:         0.250 inches         Surface Treatment:         Passivate         Surface Treatment Specification:         Astm a380 assn standard single treatment response         Style Designator:         Keylock         Thread Series Designator:         N/a         Dirt Of Measure:         N/a         Fig:	Thread Class:
Between 0.360 inches and 0.390 inches         Insert Size:         0.375-16 unc 2a         Internal Thread Relief Depth:         Between 0.165 inches and 0.185 inches         Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Features Provided:         Individually keyed         Thready Qty Per Inch (tpi):         20         Thread Size:         0.250 inches         Special Features:         Dry film lubricated         Surface Treatment:         Passivate         Surface Treatment Specification:         Astm a380 assn standard single treatment response         Style Designator:         Keylock         Thread Series Designator:         Inc         Sheff Life:         N/a         Entite:         N/a         Fined Series Designator:         Inter Of Measure:         Image:         Inter Of Measure:         Image:	3b
Insert Size: 0.375-16 unc 2a Internal Thread Relief Depth: Between 0.165 inches and 0.185 inches Full Internal Thread Length: Between 0.360 inches and 0.390 inches Features Provided: Individually keyed Thready Qty Per Inch (tpi): 20 Thread Size: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Length:
0.375-16 unc 2a Internal Thread Relief Depth: Between 0.165 inches and 0.185 inches Full Internal Thread Length: Between 0.360 inches and 0.390 inches Features Provided: Individually keyed Thready Qty Per Inch (tpi): 20 Thread Size: 0.250 inches Special Features: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Between 0.360 inches and 0.390 inches
Internal Thread Relief Depth:         Between 0.165 inches and 0.185 inches         Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Features Provided:         Individually keyed         Thready Qty Per Inch (tpi):         20         Thread Size:         0.250 inches         Special Features:         Dry film lubricated         Surface Treatment:         Passivate         Surface Treatment Specification:         Astm a380 assn standard single treatment response         Style Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            To         Sile         Fig:	Insert Size:
Between 0.165 inches and 0.185 inches Full Internal Thread Length: Between 0.360 inches and 0.390 inches Features Provided: Individually keyed Intready Qty Per Inch (tpi): 20 Thread Size: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Tomilitarization: No Fig:	0.375-16 unc 2a
Full Internal Thread Length:         Between 0.360 inches and 0.390 inches         Features Provided:         Individually keyed         Thready Qty Per Inch (tpi):         20         Thread Size:         0.250 inches         Special Features:         Dry film lubricated         Surface Treatment:         Passivate         Surface Treatment Specification:         Astm a380 assn standard single treatment response         Style Designator:         Keylock         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Internal Thread Relief Depth:
Between 0.360 inches and 0.390 inches Features Provided: Individually keyed Individually keyed Inready Qty Per Inch (tpi): 20 Inread Size: 0.250 inches Special Features: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Inread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.165 inches and 0.185 inches
Features Provided:   Individually keyed   Thready Qty Per Inch (tpi):   20   Thread Size:   0.250 inches   Special Features:   Dry film lubricated   Surface Treatment:   Passivate   Surface Treatment Specification:   Astm a380 assn standard single treatment response   Style Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Full Internal Thread Length:
Individually keyed Individually keyed Inready Qty Per Inch (tpi): 20 Inread Size: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Inread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.360 inches and 0.390 inches
Thready Qty Per Inch (tpi): 20 Thread Size: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Features Provided:
20 Thread Size: 0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Astm a380 assn standard single treatment response Style Designator: Mathered Series Designator: Unc Shelf Life: Na Demilitarization: No	Individually keyed
Thread Size:   0.250 inches   Special Features:   Dry film lubricated   Surface Treatment:   Passivate   Surface Treatment Specification:   Astm a380 assn standard single treatment response   Style Designator:   Keylock   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Thready Qty Per Inch (tpi):
0.250 inches Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	20
Special Features: Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Size:
Dry film lubricated Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.250 inches
Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Special Features:
Passivate Surface Treatment Specification: Astm a380 assm standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Fig:	Dry film lubricated
Surface Treatment Specification: Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Surface Treatment:
Astm a380 assn standard single treatment response Style Designator: Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate
Style Designator:   Keylock   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Surface Treatment Specification:
Keylock Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Astm a380 assn standard single treatment response
Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Style Designator:
Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Keylock
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Unc
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A03100	Fiig:
	A03100