

View Online at <https://aerobasegroup.com/nsn/5325-01-324-5057>

**Grip Length:**

Between 0.150 inches and 0.290 inches

**Diameter:**

Between 0.473 inches and 0.492 inches

**Securing Device Type:**

Washer

**Minor Diameter:**

Between 0.234 inches and 0.238 inches

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

Between 0.497 inches and 0.617 inches

**Turnlock Stud Head Style:**

Flat fillister

**Material Accommodated Thickness:**

Between 0.150 inches and 0.290 inches

**Drive Type:**

Socket

**Stud Head Height:**

Between 0.130 inches and 0.144 inches

**Stud Shank Major Diameter:**

Between 0.2470 inches and 0.2495 inches

**Material:**

Steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-5626 spec.