NSN 5325-01-335-6542

Turnlock Fastener Receptacle - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-335-6542

| · · · · · · · · · · · · · · · · · · · |
|--|
| Center To Center Distance Between Mounting Holes: |
| Between 1.123 inches and 1.127 inches |
| Mounting Style: |
| Plain w/mounting hole |
| Turnlock Receptacle Style: |
| Two lug floating |
| Receptaclelength: |
| 1.390 inches |
| Receptacle Height: |
| 0.396 inches |
| Receptacle Width: |
| 0.850 inches |
| Stud Protrusion Length: |
| 0.437 inches |
| Receptacle Thread Size And Series/type Designator: |
| 0.250-28 unjf |
| Turnlock Mounting Hole Diameter: |
| Between 0.130 inches and 0.135 inches |
| Material: |
| Stainless steel stud |
| Material Specification: |
| Ams 5525 assn standard single material response stud |
| Surface Treatment: |
| Passivate stud |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A05400 |