NSN 5325-01-337-2810

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-337-2810

Double oval Inside Diameter: 3,724 inches Casehardening Indicator: Not casehardened Outside Diameter: 3,875 inches Major Thickness: 0,061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40,0 rockwell c and 51.5 rockwell c Material: External Material Hardness Rating: Between 40,0 rockwell c and 51.5 rockwell c Material: Steel. miles-46049, comp 1085 or steel, miles-46049, comp 1074 or steel, miles-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Material Specification Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Cadmium, q-p-416, type 2, class 2 Shelf Life: Na Unit Of Measure: — Demilitarization: No Flig: T252-0 Milest (millitary Standard):	Cross Sectional Shape:
3.724 inches Casehardening Indicator: Not casehardened Outside Diameter: 3.875 inches Major Thickness: 0.061 inches Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mills-46049, comp 1065 or steel, mills-46049, comp 1074 or steel, mills-46049, comp 1085 Material Specification: Mills-46049, comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mills-46049, comp 1065 or steel smills specification 1st material response and mills-46049, comp 1074 military specification 2nd material response and mills-46049, comp 1074 military specification 2nd material response and mills-46049, comp 1085 Mills-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: T252-g Mill-setd (military Standard):	Double oval
Casehardening Indicator: Not casehardened Outside Diameter: 3.875 inches Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1085 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1085 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Sheft Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Inside Diameter:
Not casehardened Outside Diameter: 3.875 inches Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material! Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1085 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit of Measure: Demilitarization: No Fig: T252-g Mil-std (milltary Standard):	3.724 inches
Outside Diameter: 3.875 inches Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mill-s-46049, comp 1065 or steel, mill-s-46049, comp 1074 or steel, mill-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mill-s-46049, comp 1065 military specification 1st material response and mill-s-46049, comp 1074 military specification 2nd material response and mill-s-46049, comp 1074 military specification 2nd material response and mill-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: T252-g Mill-std (military Standard):	Casehardening Indicator:
Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Not casehardened
Major Thickness: 0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1074 military specification 2nd material response Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Outside Diameter:
0.061 inches Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: T252-9 Mil-std (military Standard):	3.875 inches
Ring Style: Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: T252-g Mil-std (military Standard):	Major Thickness:
Spiral Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1074 military specification 2nd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: Na Unit Of Measure: Demilitarization: No Fig: T252-9 Mil-std (military Standard):	0.061 inches
Usage Design: External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: Na Unit Of Measure: Demilitarization: No Filig: T252-9 Mil-std (military Standard):	Ring Style:
External Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: T252-g Mil-std (military Standard):	Spiral
Material Hardness Rating: Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: T252-g Mil-std (military Standard):	Usage Design:
Between 40.0 rockwell c and 51.5 rockwell c Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: T252-g Mil-std (military Standard):	External
Material: Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Material Hardness Rating:
Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085 Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Between 40.0 rockwell c and 51.5 rockwell c
Material: Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Material:
Steel comp 1065 or steel comp 1074 or steel comp 1085 Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Steel, mil-s-46049, comp 1065 or steel, mil-s-46049, comp 1074 or steel, mil-s-46049, comp 1085
Material Specification: Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Material:
Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-9 Mil-std (military Standard):	Steel comp 1065 or steel comp 1074 or steel comp 1085
response and mil-s-46049, comp 1085 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Material Specification:
Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mill-std (military Standard):	Mil-s-46049, comp 1065 military specification 1st material response and mil-s-46049, comp 1074 military specification 2nd material
Cadmium and chromate Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	response and mil-s-46049, comp 1085 military specification 3rd material response
Surface Treatment: Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Surface Treatment:
Cadmium, qq-p-416, type 2, class 2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Cadmium and chromate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-9 Mil-std (military Standard):	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Cadmium, qq-p-416, type 2, class 2
Unit Of Measure: Demilitarization: No Fiig: T252-g Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: T252-g Mil-std (military Standard):	N/a
No Fiig: T252-g Mil-std (military Standard):	Unit Of Measure:
No Fiig: T252-g Mil-std (military Standard):	
Fiig: T252-g Mil-std (military Standard):	Demilitarization:
T252-g Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	T252-g
Mil-s-46049 spec.	Mil-std (military Standard):
	Mil-s-46049 spec.