NSN 5325-01-355-1010

Turnlock Fastener Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5325-01-355-1010

Grip Length:

Between 0.412 inches and 0.444 inches

Center To Center Distance Between Mounting Holes:

Between 0.685 inches and 0.689 inches

Mounting Style:

Plain w/mounting hole

Body Thickness:

0.0115 inches

Securing Device Type:

Grommet

Turnlock Stud Shank Style:

Stud shank

Turnlock Eyelet Style:

Eyelet

Eyelet Height:

0.189 inches

Turnlock Receptacle Style:

Receptacle

Material Accommodated Thickness:

Between 0.110 inches and 0.139 inches

Largest Outside Diameter:

0.336 inches

Eyelet Inside Diameter:

Between 0.252 inches and 0.256 inches

Stud Shank Major Diameter:

0.375 inches

Turnlock Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Material:

Steel comp 304 grommetsteel receptaclesteel comp 8740 nut

Material Specification:

Qq-s-763 federal specification single material response grommetams5528 assn standard single material response receptaclemil-s-6049

military specification single material response nut or mil-s-5626 military specification single material response nut

Surface Treatment:

Passivate grommetpassivate receptaclecadmium nut and chromate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response grommetqq-p-35 federal specification single treatment response receptacleqq-p-416,

type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5325-01-355-1010

Turnlock Fastener Assembly - Page 2 of 2



Fiig: A05400

Mil-std (military Standard):

Mil-s-6049 spec.