NSN 5325-01-357-9477

Turnlock Fastener Receptacle - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-357-9477

| Center To Center Distance Between Mounting Holes: |
|--|
| Between 0.705 inches and 0.709 inches |
| Mounting Style: |
| Plain w/mounting hole |
| Distance Between Mounting Hole Centers: |
| Between 0.495 inches and 0.505 inches |
| Turnlock Receptacle Style: |
| Receptacle |
| Receptaclelength: |
| 1.033 inches |
| Receptacle Height: |
| 0.430 inches |
| Stud Protrusion Length: |
| 0.250 inches |
| Receptacle Thread Size And Series/type Designator: |
| 0.190-32 unf |
| Turnlock Mounting Hole Diameter: |
| Between 0.098 inches and 0.103 inches |
| Material: |
| Iron alloy 660 retaineriron alloy 660 stud |
| Material Specification: |
| Ams 5525 assn standard single material response |
| Precious Material And Location: |
| Stud silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Passivate barrelpassivate retainersilver stud |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response barrelqq-p-35 federal specification single treatment response retainerams 2410 ass |
| standard single treatment response stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A05400 |
| |