

View Online at <https://aerobasegroup.com/nsn/5325-01-358-5612>

Grip Length:

0.511 inches

Diameter:

Between 0.330 inches and 0.350 inches

Securing Device Type:

Grommet

Turnlock Stud Shank Style:

Stud shank

Extension Length:

0.080 inches

Turnlock Stud Head Style:

Flat countersunk

Material Accommodated Thickness:

Between 0.257 inches and 0.330 inches

Drive Type:

Socket

Stud Thread Size And Series/type Designator:

0.164-32 unc

Stud Shank Major Diameter:

Between 0.2470 inches and 0.2495 inches

Special Features:

4 lead thd; grommet 0.569 in. Od, 0.110 in. Min, 0.120 in. Maximum thk made around stud with locking element

Material:

Steel comp 630 retainer or steel retainersteel comp 630 stud

Material Specification:

Ams 5529 assn standard 1st material response retainer or mil-s-25043 military specification 2nd material response retainer or ams 5644 assn standard 2nd material response retainerams5643 assn standard single material response stud

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A05400

Mil-std (military Standard):

Mil-s-25043 spec.