

View Online at <https://aerobasegroup.com/nsn/5325-01-358-5612>

**Grip Length:**

0.511 inches

**Diameter:**

Between 0.330 inches and 0.350 inches

**Securing Device Type:**

Grommet

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

0.080 inches

**Turnlock Stud Head Style:**

Flat countersunk

**Material Accommodated Thickness:**

Between 0.257 inches and 0.330 inches

**Drive Type:**

Socket

**Stud Thread Size And Series/type Designator:**

0.164-32 unc

**Stud Shank Major Diameter:**

Between 0.2470 inches and 0.2495 inches

**Special Features:**

4 lead thd; grommet 0.569 in. Od, 0.110 in. Min, 0.120 in. Maximum thk made around stud with locking element

**Material:**

Steel comp 630 retainer or steel retainersteel comp 630 stud

**Material Specification:**

Ams 5529 assn standard 1st material response retainer or mil-s-25043 military specification 2nd material response retainer or ams 5644 assn standard 2nd material response retainerams5643 assn standard single material response stud

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-25043 spec.