

View Online at <https://aerobasegroup.com/nsn/5325-01-362-4520>

**Center To Center Distance Between Mounting Holes:**

Between 0.748 inches and 0.752 inches

**Mounting Style:**

Plain w/mounting hole

**Turnlock Receptacle Style:**

Receptacle

**Receptacle length:**

1.017 inches

**Receptacle Height:**

0.770 inches

**Receptacle Width:**

0.625 inches

**Receptacle Thread Size And Series/type Designator:**

0.190-32 unjf

**Turnlock Mounting Hole Diameter:**

0.125 inches

**Material:**

Iron alloy 660 barrel iron alloy 660 retainer iron alloy 660 stud steel comp 303 washer

**Material Specification:**

Ams 5732 assn standard single material response barrel ams 5725 assn standard single material response retainer ams 5732 assn standard single material response stud mil-s-7720 military specification single material response washer

**Precious Material And Location:**

Stud silver and barrel silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver barrel passivate retainers silver stud passivate washer

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response barrel qq-p-35 federal specification single treatment response retainer ams 2410 assn standard single treatment response stud qq-p-35 federal specification single treatment response washer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-7720 spec.