

View Online at <https://aerobasegroup.com/nsn/5325-01-365-0603>

**Center To Center Distance Between Mounting Holes:**

Between 0.748 inches and 0.752 inches

**Mounting Style:**

Plain w/mounting hole

**Turnlock Receptacle Style:**

Two lug floating

**Receptacle length:**

1.017 inches

**Receptacle Height:**

0.712 inches

**Receptacle Width:**

0.625 inches

**Stud Protrusion Length:**

0.250 inches

**Receptacle Thread Size And Series/type Designator:**

0.164-32 unjc

**Turnlock Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Material:**

Iron alloy 660 barreliron alloy 660 retaineriron alloy 660 stud

**Material Specification:**

Ams5525 assn standard single material response barrel or ams5732 assn standard single material response barrel or ams5737 assn standard single material response barrelams5525 assn standard single material response retainer or ams5732 assn standard single material response retainer or ams5737 assn standard single material response retainerams5525 assn standard single material response stud or ams5732 assn standard single material response stud or ams5737 assn standard single material response stud

**Precious Material And Location:**

Stud silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate barrelcadmium retainer and chromate retainerpassivate stud and silver stud

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response barrelqq-p-416, ty2, cl2 federal specification single treatment response retainerrqq-p-35 federal specification 1st treatment response stud and ams2410 assn standard 2nd treatment response stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A05400