

View Online at <https://aerobasegroup.com/nsn/5325-01-365-0603>

Center To Center Distance Between Mounting Holes:

Between 0.748 inches and 0.752 inches

Mounting Style:

Plain w/mounting hole

Turnlock Receptacle Style:

Two lug floating

Receptacle length:

1.017 inches

Receptacle Height:

0.712 inches

Receptacle Width:

0.625 inches

Stud Protrusion Length:

0.250 inches

Receptacle Thread Size And Series/type Designator:

0.164-32 unjc

Turnlock Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Material:

Iron alloy 660 barreliron alloy 660 retaineriron alloy 660 stud

Material Specification:

Ams5525 assn standard single material response barrel or ams5732 assn standard single material response barrel or ams5737 assn standard single material response barrelams5525 assn standard single material response retainer or ams5732 assn standard single material response retainer or ams5737 assn standard single material response retainerams5525 assn standard single material response stud or ams5732 assn standard single material response stud or ams5737 assn standard single material response stud

Precious Material And Location:

Stud silver

Precious Material:

Silver

Surface Treatment:

Passivate barrelcadmium retainer and chromate retainerpassivate stud and silver stud

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response barrelqq-p-416, ty2, cl2 federal specification single treatment response retainerrqq-p-35 federal specification 1st treatment response stud and ams2410 assn standard 2nd treatment response stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A05400