

View Online at <https://aerobasegroup.com/nsn/5325-01-365-1301>

**Center To Center Distance Between Mounting Holes:**

Between 0.748 inches and 0.752 inches

**Mounting Style:**

Plain w/mounting hole

**Turnlock Receptacle Style:**

Two lug floating

**Receptacle length:**

1.017 inches

**Receptacle Height:**

0.712 inches

**Receptacle Width:**

0.625 inches

**Stud Protrusion Length:**

0.125 inches

**Turnlock Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Material:**

Iron alloy 660 barrel iron alloy 660 retainer iron alloy 660 stud

**Material Specification:**

Ams5525 assn standard single material response barrel or ams5732 assn standard single material response barrel or ams5737 assn standard single material response barrel ams5525 assn standard single material response retainer or ams5732 assn standard single material response retainer or ams5737 assn standard single material response retainer ams5525 assn standard single material response stud or ams5732 assn standard single material response stud or ams5737 assn standard single material response stud

**Precious Material And Location:**

Stud silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate barrel cadmium retainer and chromate retainer passivate stud and silver stud

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response barrel qq-p-416, ty2, cl2 federal specification single treatment response retainer qq-p-35 federal specification 1st treatment response stud and ams2410 assn standard 2nd treatment response stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400