

View Online at <https://aerobasegroup.com/nsn/5325-01-365-1304>

**Center To Center Distance Between Mounting Holes:**

Between 0.873 inches and 0.877 inches

**Mounting Style:**

Plain w/mounting hole

**Turnlock Receptacle Style:**

Two lug floating

**Receptacle length:**

1.143 inches

**Receptacle Height:**

0.692 inches

**Receptacle Width:**

0.741 inches

**Stud Protrusion Length:**

0.187 inches

**Turnlock Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Material:**

Iron alloy 660

**Material Specification:**

Ams5525 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

**Precious Material And Location:**

Stud silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate barrelcadmium retainer and chromate retainerpassivate stud and silver stud

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response barrelqq-p-416, ty2, cl2 federal specification single treatment response retainerqq-p-35 federal specification 1st treatment response stud and ams2410 assn standard 2nd treatment response stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400