## NSN 5325-01-365-4993

A05400

Turnlock Fastener Receptacle - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5325-01-365-4993   |
|---|
| Center To Center Distance Between Mounting Holes:   |
| Between 0.705 inches and 0.709 inches   |
| Mounting Style:   |
| Plain w/mounting hole   |
| Distance Between Mounting Hole Centers:   |
| Between 0.495 inches and 0.505 inches   |
| Turnlock Receptacle Style:  |
| Receptacle  |
| Receptaclelength:   |
| 1.050 inches  |
| Receptacle Height:  |
| 0.771 inches  |
| Stud Protrusion Length:   |
| 0.125 inches  |
| Receptacle Thread Size And Series/type Designator:  |
| 0.250-28 unjf   |
| Turnlock Mounting Hole Diameter:  |
| Between 0.130 inches and 0.135 inches   |
| Material:   |
| Steel comp 8740 barrelsteel comp 1050 retainersteel comp 8740 stud  |
| Material Specification:   |
| Ams 6322 assn standard single material response barrelaisi assn standard single material response retainerams 6322 assn standard single   |
| material response stud  |
| Surface Treatment:  |
| Cadmium barrel and chromate barrelcadmium retainer and chromate retainercadmium stud and chromate stud                                    |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 2 federal specification single treatment response barrelqq-p-416, type 2 cl 2 federal specification single treatment |
| response retainerqq-p-416, type 2, cl 2 federal specification single treatment response stud  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |