

View Online at <https://aerobasegroup.com/nsn/5325-01-365-4993>

**Center To Center Distance Between Mounting Holes:**

Between 0.705 inches and 0.709 inches

**Mounting Style:**

Plain w/mounting hole

**Distance Between Mounting Hole Centers:**

Between 0.495 inches and 0.505 inches

**Turnlock Receptacle Style:**

Receptacle

**Receptaclelength:**

1.050 inches

**Receptacle Height:**

0.771 inches

**Stud Protrusion Length:**

0.125 inches

**Receptacle Thread Size And Series/type Designator:**

0.250-28 unjf

**Turnlock Mounting Hole Diameter:**

Between 0.130 inches and 0.135 inches

**Material:**

Steel comp 8740 barrelsteel comp 1050 retainersteel comp 8740 stud

**Material Specification:**

Ams 6322 assn standard single material response barrelaisi assn standard single material response retainerams 6322 assn standard single material response stud

**Surface Treatment:**

Cadmium barrel and chromate barrelcadmium retainer and chromate retainercadmium stud and chromate stud

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response barrelqq-p-416, type 2 cl 2 federal specification single treatment response retainerqq-p-416, type 2, cl 2 federal specification single treatment response stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A05400