

View Online at <https://aerobasegroup.com/nsn/5325-01-370-9454>

Cross Sectional Shape:

Rectangular

Inside Diameter:

3.584 inches

Casehardening Indicator:

Not casehardened

Major Thickness:

0.109 inches

Ring Style:

External

Usage Design:

External

Material Hardness Rating:

Between 44.0 rockwell c and 49.0 rockwell c

Material:

Steel, astm a682, grade 1064 or steel, astm a682, grade 1065 or steel, astm a682, grade 1070 or steel, astm a682, grade 1074 or steel, astm a682, grade 1080 or steel, astm a682, grade 1085 or steel, astm a682, grade 1086 or steel, astm a682, grade 1095 or steel, ams 5520

Material:

Steel comp 1064 or steel comp 1065 or steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 1086 or steel comp 1095 or steel comp 632

Material Specification:

Astm a682, grade 1064 assn standard 1st material response and astm a682, grade 1065 assn standard 2nd material response and astm a682, grade 1070 assn standard 3rd material response and astm a682, grade 1074 assn standard 4th material response and astm a682, grade 1080 assn standard 5th material response and astm a682, grade 1085 assn standard 6th material response and astm a682, grade 1086 assn standard 7th material response and astm a682, grade 1095 assn standard 8th material response and ams 5520 assn standard 9th material response

Surface Treatment:

Cadmium and chromate or zinc and chromate or phosphate zinc

Surface Treatment:

Cadmium, qq-p-416, type 2, class 3 or zinc, astm b633, type 2 or phosphate, dod-p-16232, type z, class 2

Specification Data:

96906-ms16624 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-g