

View Online at <https://aerobasegroup.com/nsn/5325-01-381-9746>

**Cross Sectional Shape:**

Rectangular

**Inside Diameter:**

Between 0.234 inches and 0.240 inches

**Casehardening Indicator:**

Not casehardened

**Major Thickness:**

Between 0.032 inches and 0.038 inches

**Ring Style:**

External

**Usage Design:**

External

**Material Hardness Rating:**

Between 65.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n

**Material:**

Steel, astm a682, grade 1060 or steel, astm a682, grade 1064 or steel, astm a682, grade 1065 or steel, astm a682, grade 1070 or steel, astm a682, grade 1074 or steel, astm a682, grade 1080 or steel, astm a682, grade 1085 or steel, astm a682, grade 1086 or steel, astm a682, grade 1095

**Material:**

Steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 1086 or steel comp 1095

**Material Specification:**

Astm a682, grade 1060 assn standard 1st material response and astm a682, grade 1064 assn standard 2nd material response and astm a682, grade 1065 assn standard 3rd material response and astm a682, grade 1070 assn standard 4th material response and astm a682, grade 1074 assn standard 5th material response and astm a682, grade 1080 assn standard 6th material response and astm a682, grade 1085 assn standard 7th material response and astm a682, grade 1086 assn standard 8th material response and astm a682, grade 1095 assn standard 9th material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment:**

Zinc, astm b633, type 2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-g