

View Online at <https://aerobasegroup.com/nsn/5325-01-386-1504>

Cross Sectional Shape:

Rectangular

Inside Diameter:

5.4955 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

Between 5.993 inches and 5.998 inches

Major Thickness:

Between 0.034 inches and 0.040 inches

End Style:

Vertex center or above

Ring Style:

Internal

Usage Design:

External or internal

Strength Rating:

211000.0 pounds per square inch tensile

Special Features:

Slot on each end, 0.280 in. Long by 0.060 in. Wide, 0.265 in. Min to 0.295 in. Maximum distance from ends, 0.060 in. From o.D. Face; 1.060 in. Min to 1.180 in. Maximum free gap

Material:

Steel, sae 1070 or steel, sae 1072 or steel, sae 1074 or steel, sae 1075 or steel, sae 1078 or steel, sae 1080 or steel, sae 1084 or steel, sae 1086 or steel, sae 1090

Material:

Steel, sae 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp 1080 or steel comp 1084 or steel comp 1086 or steel comp 1090

Material Specification:

Sae 1072 assn standard 2nd material response and sae 1074 assn standard 3rd material response and sae 1075 assn standard 4th material response and sae 1078 assn standard 5th material response and sae 1080 assn standard 6th material response and sae 1084 assn standard 7th material response and sae 1086 assn standard 8th material response and sae 1090 assn standard 9th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment:

Cadmium, qq-p-416, type 2, class 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-g