## NSN 5325-01-399-0382

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-399-0382

Cross Sectional Shape:
Rectangular
Inside Diameter:
4.510 inches
Casehardening Indicator:
Not casehardened
Outside Diameter:
4.900 inches
Major Thickness:
Between 0.060 inches and 0.061 inches
End Style:
90 degree parallel
Ring Style:
Straight gap
Usage Design:
Internal
Material:
Steel, ams 5528 or steel, mil-s-25043
Material:
Steel comp 631 or steel comp 631
Material Specification:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:
Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  T252-9