NSN 5325-01-399-0385

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-399-0385

Cross Sectional Shape:
Rectangular
Inside Diameter:
4.485 inches
Casehardening Indicator:
Not casehardened
Outside Diameter:
4.875 inches
Major Thickness:
Between 0.044 inches and 0.045 inches
End Style:
90 degree parallel
Ring Style:
Straight gap
Usage Design:
Internal
Material:
Steel, ams 5528 or steel, mil-s-25043
Material:
Steel comp 631 or steel comp 631
Steel comp 631 or steel comp 631 Material Specification:
Material Specification:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Material Specification: Ams 5528 assn standard 1st material response and mil-s-25043 military specification 2nd material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g