

View Online at <https://aerobasegroup.com/nsn/5325-01-429-4914>

**Grip Length:**

0.430 inches

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

Between 0.195 inches and 0.225 inches

**Turnlock Stud Head Style:**

Hexagon countersunk

**Stud Thread Size And Series/type Designator:**

0.1640-32 unc

**Width Across Flats:**

Between 0.385 inches and 0.475 inches

**Stud Head Height:**

Between 0.545 inches and 0.575 inches

**Stud Shank Major Diameter:**

Between 0.2470 inches and 0.2495 inches

**Special Features:**

Stud head is .156 hex recess to depth shown .270-.330 dis. X 120 degrees c'sink, stud shank .040 wide x .026 deep splines 120 degrees apart 3 plcs.. Thsd .1640-32unc-3b , 4 lead thd.

**Material:**

Steel comp 301 barrel and steel comp 302 barrel and steel comp 303 barrel and steel comp 303cu barrel and steel comp 303ma barrel and steel comp 303se barrel and steel comp 304 barrel and steel comp 305 barrel and steel comp 316 barrel

**Surface Treatment:**

Passivate barrel

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response barrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400