

View Online at <https://aerobasegroup.com/nsn/5325-01-445-6437>

**Grommetlength:**

Between 9.20 inches and 9.60 inches

**Product Name:**

Seal, coated airlift to hood, rh

**Special Features:**

weight change antifreeze: +3.0% iaw a-a-52624, one-to-one volume mixture with water, brake fluid (iaw mil-prf-46176): +25.0%, diesel fuel (iaw a-a-52557) +10.0%, lubricating oil, gear (grade 80w-90, iaw sae j23601: +2.0%, lubricating oil, engine (grade 30, iaw mil-prf-2104: +2.0%, salt water (3.5%): +3.0%, transmission fluid: +5.0%, water (distilled): +3.0%, windshield washer solvent: iaw a-a-59664, type i: +5.0%,

**Material:**

Rubber synthetic

**Special Test Features:**

Coating thickness of synthetic rubber shall be .015" to .040", additional coating thickness in radii is permissible

**Specification Data:**

96906-dod-std-00100 (ar) government standard and 80204-ansi y14.5m-1982 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-prf-46176 spec.