

View Online at <https://aerobasegroup.com/nsn/5325-01-505-0369>

Grip Length:

Between 0.344 inches and 0.437 inches

Diameter:

Between 0.257 inches and 0.373 inches

Center To Center Distance Between Mounting Holes:

Between 0.682 inches and 0.692 inches

Mounting Style:

Plain w/mounting hole

Turnlock Stud Shank Style:

Stud shank

Extension Length:

Between 0.178 inches and 0.198 inches

Turnlock Stud Head Style:

Stud head

Turnlock Receptacle Style:

Receptacle

Receptaclelength:

0.938 inches

Receptacle Height:

Between 0.545 inches and 0.575 inches

Receptacle Width:

Between 0.425 inches and 0.455 inches

Stud Thread Size And Series/type Designator:

0.1640-32 unc

Stud Head Height:

Between 0.105 inches and 0.120 inches

Stud Shank Major Diameter:

Between 0.247 inches and 0.249 inches

Turnlock Mounting Hole Diameter:

Between 0.250 inches and 0.255 inches

Special Features:

Receptacle p/n ca1810, ca1825, or ca1826-1. Head has size 10 cross recess

Material:

Steel comp 303se barrel or steel comp 303 barrel

Material Specification:

Ams 5789 assn standard single material response barrel and ams 5640 assn standard single material response barrel and astm-a-581 assn standard single material response barrel and astm-a-582 assn standard single material response barrel

Surface Treatment:

Passivate barrel

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response barrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A05400