

View Online at <https://aerobasegroup.com/nsn/5325-01-506-8717>

**Grip Length:**

Between 0.125 inches and 0.187 inches

**Diameter:**

Between 0.256 inches and 0.270 inches

**Securing Device Type:**

Ring

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

Between 0.125 inches and 0.187 inches

**Turnlock Stud Head Style:**

Fillister

**Material Accommodated Thickness:**

Between 0.125 inches and 0.187 inches

**Drive Type:**

Socket

**Stud Thread Size And Series/type Designator:**

0.112-40 unc

**Stud Shank Major Diameter:**

Between 0.184 inches and 0.186 inches

**Special Features:**

HEXS-OC-KET-DEEP

**Material:**

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 316

**Material Specification:**

Mil-s-7720 military specification 1st material response or astma582 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 4 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-7720 spec.