

View Online at <https://aerobasegroup.com/nsn/5325-01-524-9378>

**Diameter:**

0.500 inches

**Securing Device Type:**

Washer

**Turnlock Stud Head Style:**

Fillister

**Stud Assembly Style:**

Stud assembly

**Distance From Engaging Member To Largest Bearing Surface Of Head:**

0.870 inches

**Eyelet Outside Diameter:**

0.246 inches

**Eyelet Length:**

0.320 inches

**Material Accommodated Thickness:**

Between 0.360 inches and 0.389 inches

**Drive Type:**

Cross recess

**Material:**

Steel comp 4037 stud or steel comp 1008 stud or steel comp 1010 stud or steel comp 8740 stud

**Material Specification:**

Ams 6300 assn standard 1st material response stud or astm a108 assn standard 2nd material response stud or astm a108 assn standard 3rd material response stud or mil-s-6049 military specification 4th material response stud

**Surface Treatment:**

Cadmium stud

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-6049 spec.