

View Online at <https://aerobasegroup.com/nsn/5325-01-567-3747>

Grip Length:

Between 0.851 inches and 0.920 inches

Diameter:

Between 0.394 inches and 0.404 inches

Securing Device Type:

Ring

End Application:

Radar radome; challenger cl-604

Turnlock Stud Shank Style:

Stud shank

Extension Length:

Between 0.195 inches and 0.225 inches

Turnlock Stud Head Style:

Flat countersunk

Drive Type:

Socket

Stud Thread Size And Series/type Designator:

0.164-32 unc

Stud Shank Major Diameter:

Between 0.211 inches and 0.231 inches

Product Name:

Stud nut hold out type

Special Features:

Hex recess on head; total length of stud 1.130inches; ultimate shear 1815 lbs through hex recess and 2200 lbs through shank; ultimate tensile 1900 lbs ; heat treated 160ksi per mil-h-6875

Material:

Steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A05400

Mil-std (military Standard):

Mil-s-6049 spec.