

View Online at <https://aerobasegroup.com/nsn/5325-01-567-3747>

**Grip Length:**

Between 0.851 inches and 0.920 inches

**Diameter:**

Between 0.394 inches and 0.404 inches

**Securing Device Type:**

Ring

**End Application:**

Radar radome; challenger cl-604

**Turnlock Stud Shank Style:**

Stud shank

**Extension Length:**

Between 0.195 inches and 0.225 inches

**Turnlock Stud Head Style:**

Flat countersunk

**Drive Type:**

Socket

**Stud Thread Size And Series/type Designator:**

0.164-32 unc

**Stud Shank Major Diameter:**

Between 0.211 inches and 0.231 inches

**Product Name:**

Stud nut hold out type

**Special Features:**

Hex recess on head; total length of stud 1.130inches; ultimate shear 1815 lbs through hex recess and 2200 lbs through shank; ultimate tensile 1900 lbs ; heat treated 160ksi per mil-h-6875

**Material:**

Steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-6049 spec.