# NSN 5325-01-616-4653

Screw Thread Insert - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5325-01-616-4653

## Thread Class:

3b

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.242 inches

## Length:

Between 0.297 inches and 0.327 inches

#### **Overall Length:**

0.442 inches

#### **End Application:**

7010-01-479-3095

#### Insert Size:

0.4375-14unc-2a

#### Internal Thread Relief Depth:

Between 0.060 inches and 0.080 inches

## Full Internal Thread Length:

0.242 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## **Special Features:**

Insert is supplied with (2) locking keys spaced 180 degrees apart. Locking keys are steel, corrosion resistant, type 302 per astm a580/a580m

## Material:

Steel comp 303 or steel comp 303se

## **Material Specification:**

Sae ams5640 assn standard 1st material response or astm a582/a528m assn standard 1st material response or sae ams5640 assn standard 2nd material response or sae ams5738 assn standard 2nd material response or sae ams5738 assn standard 2nd material response

## Surface Treatment:

Passivate

## **Surface Treatment Specification:**

Sae ams2700 assn standard single treatment response

#### Style Designator:

Keylock

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

- --
- Demilitarization:

# NSN 5325-01-616-4653

Screw Thread Insert - Page 2 of 2

**Fiig:** A03100

