

View Online at <https://aerobasegroup.com/nsn/5325-01-625-3874>

Diameter:

Between 0.377 inches and 0.384 inches

End Application:

Ch-53a/d/e

Turnlock Stud Head Style:

Stud head

Stud Assembly Style:

Stud assembly

Distance From Engaging Member To Largest Bearing Surface Of Head:

Between 0.683 inches and 0.693 inches

Eyelet Outside Diameter:

Between 0.341 inches and 0.348 inches

Eyelet Length:

0.472 inches

Material Accommodated Thickness:

Between 0.231 inches and 0.380 inches

Drive Type:

Cross recess

Stud Head Height:

0.102 inches

Product Name:

Stud assembly flat head cross recess

Special Features:

Spacer material is 300 series cres per astm a666 or astm a240; spring material is 302 cres per astm a313 or ams-qq-s-763; cup material is 300 series cres per astm a167, astm a240, astm a582 or astm a666

Material:

Stainless steel stud

Material Specification:

Astm a313 assn standard single material response or ams-qq-s-763 federal specification single material response pin

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a967 assn standard single treatment response or ams2700 national std/spec single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A05400