

View Online at <https://aerobasegroup.com/nsn/5325-01-625-3874>

**Diameter:**

Between 0.377 inches and 0.384 inches

**End Application:**

Ch-53a/d/e

**Turnlock Stud Head Style:**

Stud head

**Stud Assembly Style:**

Stud assembly

**Distance From Engaging Member To Largest Bearing Surface Of Head:**

Between 0.683 inches and 0.693 inches

**Eyelet Outside Diameter:**

Between 0.341 inches and 0.348 inches

**Eyelet Length:**

0.472 inches

**Material Accommodated Thickness:**

Between 0.231 inches and 0.380 inches

**Drive Type:**

Cross recess

**Stud Head Height:**

0.102 inches

**Product Name:**

Stud assembly flat head cross recess

**Special Features:**

Spacer material is 300 series cres per astm a666 or astm a240; spring material is 302 cres per astm a313 or ams-qq-s-763; cup material is 300 series cres per astm a167, astm a240, astm a582 or astm a666

**Material:**

Stainless steel stud

**Material Specification:**

Astm a313 assn standard single material response or ams-qq-s-763 federal specification single material response pin

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a967 assn standard single treatment response or ams2700 national std/spec single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400