NSN 5325-01-653-9820

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-653-9820

Cross Sectional Shape: Rectangular Inside Diameter: Between 0.511 inches and 0.526 inches Casehardening Indicator: Not casehardened Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design: External
Inside Diameter: Between 0.511 inches and 0.526 inches Casehardening Indicator: Not casehardened Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Between 0.511 inches and 0.526 inches Casehardening Indicator: Not casehardened Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Casehardening Indicator: Not casehardened Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Not casehardened Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Major Thickness: Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Between 0.031 inches and 0.039 inches Ring Style: External Usage Design:
Ring Style: External Usage Design:
External Usage Design:
Usage Design:
External
Material Hardness Rating:
Between 68.5 rockwell superficial 30-t and 73.0 rockwell superficial 30-t
Strength Rating:
910.0 pounds per square inch yield
Material:
Steel comp 1060 or steel comp 1090
Material Specification:
Astm-a-568/568m assn standard single material response and astm-a-684/a684m assn standard single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-dtl-16232, type z, class 2 military standard single treatment response
Specification Data:
Ms16624d government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T252-g
Mil-std (military Standard):
Mil-dtl-16232 spec.