

View Online at <https://aerobasegroup.com/nsn/5330-00-052-4399>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

Between 0.115 inches and 0.135 inches

**Overall Length:**

Between 1.160 inches and 1.220 inches

**Overall Width:**

Between 1.160 inches and 1.220 inches

**Aperture Diameter:**

Between 0.910 inches and 0.930 inches

**Outside Corner Radius:**

Between 0.060 inches and 0.100 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.901 inches and 0.911 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 0.901 inches and 0.911 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.130 inches and 0.155 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.130 inches and 0.155 inches

**Cross-sectional Thickness:**

0.032 inches

**Bolt Hole Quantity:**

4

**Material:**

Asbestos and rubber natural or rubber synthetic

**Material Specification:**

Mil-a-7021, cl 1 military specification all material responses

**Style Designator:**

Non-circular

**Fsc Application Data:**

Starters, engine, air turbine, aircraft and guided missile prime mover type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-a-7021 spec.