

View Online at <https://aerobasegroup.com/nsn/5330-00-052-4399>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.115 inches and 0.135 inches

Overall Length:

Between 1.160 inches and 1.220 inches

Overall Width:

Between 1.160 inches and 1.220 inches

Aperture Diameter:

Between 0.910 inches and 0.930 inches

Outside Corner Radius:

Between 0.060 inches and 0.100 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.901 inches and 0.911 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.901 inches and 0.911 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.130 inches and 0.155 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.130 inches and 0.155 inches

Cross-sectional Thickness:

0.032 inches

Bolt Hole Quantity:

4

Material:

Asbestos and rubber natural or rubber synthetic

Material Specification:

Mil-a-7021, cl 1 military specification all material responses

Style Designator:

Non-circular

Fsc Application Data:

Starters, engine, air turbine, aircraft and guided missile prime mover type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-a-7021 spec.