## NSN 5330-00-063-9183

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-063-9183

| Cross Sectional Shape:                                     |
|--|
| Solid single or composition                                |
| Hole Diameter:   |
| 0.187 inches   |
| Overall Length:  |
| 7.000 inches   |
| Overall Width:   |
| 2.125 inches   |
| Aperture Width:  |
| 1.625 inches   |
| Aperture Length:   |
| 6.500 inches   |
| Inside Corner Bevel Length Along Width:                    |
| 0.312 inches   |
| Inside Corner Bevel Length Along Length:                   |
| 0.312 inches   |
| Center To Center Distance Between Bolt Holes Along Width:  |
| 1.625 inches   |
| Center To Center Distance Between Bolt Holes Along Length: |
| 6.500 inches   |
| Outside Edge To Bolt Hole Center Distance Along Width:     |
| 0.250 inches   |
| Outside Edge To Bolt Hole Center Distance Along Length:    |
| 0.250 inches   |
| Cross-sectional Thickness:                                 |
| 0.062 inches   |
| Bolt Hole Quantity:  |
| 4  |
| Elongation Percentage:                                     |
| 300  |
| Hardness Rating:   |
| 35.0 shore durometer a and 55.0 shore durometer a          |
| Material:  |
| Rubber butadiene-acrylonitrile class nbr                   |
| Material Specification:                                    |
| Mil-r-2765 military specification single material response |
| Style Designator:  |
| Non-circular   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5330-00-063-9183

Gasket - Page 2 of 2



| _  |   |   |   |   |   |     |    |   |   |  |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | • | iza | 31 | ^ | n |  |
|    |   |   |   |   |   |     |    |   |   |  |

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-2765 spec.