## NSN 5330-00-072-9568

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-072-9568

| Cross Sectional Shape:  |
|---|
| Solid single or composition   |
| Hole Diameter:  |
| 0.281 inches  |
| Overall Length:   |
| 15.750 inches   |
| Overall Width:  |
| 15.750 inches   |
| Inside Corner Radius:   |
| 0.125 inches  |
| Outside Corner Radius:  |
| 0.750 inches  |
| Aperture Width:   |
| 14.000 inches   |
| Aperture Length:  |
| 14.000 inches   |
| Center To Center Distance Between Bolt Holes Along Width:               |
| 3.000 inches  |
| Center To Center Distance Between Bolt Holes Along Length:              |
| 3.000 inches  |
| Outside Edge To Bolt Hole Center Distance Along Width:                  |
| 1.875 inches  |
| Outside Edge To Bolt Hole Center Distance Along Length:                 |
| 1.875 inches  |
| Cross-sectional Thickness:  |
| Between 0.052 inches and 0.072 inches                                   |
| Bolt Hole Quantity:   |
| 20  |
| Hardness Rating:  |
| 55.0 shore durometer a and 65.0 shore durometer a                       |
| Material:   |
| Rubber chloroprene class cr   |
| Material Specification:   |
| Mil-r-6855, cl 2, gr 60 military specification single material response |
| Style Designator:   |
| Non-circular  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5330-00-072-9568

Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6855 spec.