NSN 5330-00-171-5043

Packing Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-171-5043

Cross Sectional Shape: Square Cross-sectional Thickness: Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard): Mil-r-8791 spec.	
Cross-sectional Thickness: Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Cross Sectional Shape:
Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Square
Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Cross-sectional Thickness:
Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.025 inches and 0.029 inches
Distance Between Ends: Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Cross-sectional Height:
Between 0.093 inches and 0.250 inches Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.075 inches and 0.087 inches
Center Hole Diameter: 3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Distance Between Ends:
3.125 inches Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.093 inches and 0.250 inches
Peripheral Diameter: Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Center Hole Diameter:
Between 3.363 inches and 3.367 inches Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	3.125 inches
Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Peripheral Diameter:
Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 3.363 inches and 3.367 inches
Angle: Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Joint Type:
Between 25.0 degrees and 35.0 degrees Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Scarf-butt retainer
Material: Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Angle:
Plastic polytetrafluoroethylene Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 25.0 degrees and 35.0 degrees
Material Specification: Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-r-8791 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Plastic polytetrafluoroethylene
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-r-8791 military specification single material response
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-r-8791 spec.	Mil-std (military Standard):
	Mil-r-8791 spec.