NSN 5330-00-171-6749

Packing Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-171-6749

| Cross Sectional Shape: Square Cross-sectional Thickness: Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: Between 25.0 degrees and 35.0 degrees |
|---|
| Cross-sectional Thickness: Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Between 0.025 inches and 0.029 inches Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Cross-sectional Height: Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Between 0.075 inches and 0.087 inches Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Distance Between Ends: Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Between 0.047 inches and 0.093 inches Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Center Hole Diameter: 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| 1.000 inches Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Peripheral Diameter: Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Between 1.240 inches and 1.244 inches End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| End Application: W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| W/s: main feed pumps; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-18a, ec-18b; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-42 & 45; helicopter, mh-53e; ssbn mk-118 fire control sys deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| deep submergenc systems programs (dssp) Joint Type: Scarf-butt retainer Angle: |
| Joint Type: Scarf-butt retainer Angle: |
| Scarf-butt retainer Angle: |
| Angle: |
| |
| Between 25.0 degrees and 35.0 degrees |
| |
| Material: |
| Plastic polytetrafluoroethylene |
| Material Specification: |
| Mil-r-8791 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |
| Mil-r-8791 spec. |
| |