NSN 5330-00-182-3696

Gasket - Page 1 of 1

Mil-s-5059 spec.



View Online at https://aerobasegroup.com/nsn/5330-00-182-3696

| Cross Sectional Shape: |
|---|
| Metal and synthetic rubber |
| Hole Diameter: |
| Between 0.261 inches and 0.276 inches |
| Tempurature Rating: |
| -20.0 degrees fahrenheit and 400.0 degrees fahrenheit |
| Bolt Circle Diameter: |
| 2.342 inches |
| Overall Width: |
| 2.874 inches |
| Aperture Diameter: |
| 1.138 inches |
| Outside Corner Radius: |
| 0.266 inches |
| Side Radius From Gasket Center: |
| 0.922 inches |
| Cross-sectional Thickness: |
| 0.132 inches |
| Gage Ring Thickness: |
| Between 0.084 inches and 0.100 inches |
| Bolt Hole Quantity: |
| 4 |
| Elongation Percentage: |
| 125 |
| Hardness Rating: |
| 70.0 shore durometer a and 80.0 shore durometer a |
| Material: |
| Rubber fluorocarbon class fpm and steel comp 302 |
| Material Specification: |
| Mil-s-5059, comp 302 annealed military specification 1st material response and mil-r-83248, type ii, class 1 military specification 2nd |
| material response |
| Style Designator: |
| Non-circular Section 1. The section |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |