NSN 5330-00-239-2900

Spiral Wound Gasket - Page 1 of 1



m/nsn/5330-00-239-2900

View Online at https://aerobasegroup.com
Cross Sectional Shape:
Metal winding w/ soft filler and outer ring
Tempurature Rating:
875.0 degrees fahrenheit
Outside Diameter:
Between 8.188 inches and 8.250 inches
Aperture Diameter:
Between 6.859 inches and 6.891 inches
Bearing Surface Width:
0.609 inches
Gage Ring Outside Diameter:
9.688 inches
Cross-sectional Thickness:
Between 0.170 inches and 0.180 inches
Gage Ring Thickness:
Gage Ring Thickness: Between 0.119 inches and 0.131 inches
Between 0.119 inches and 0.131 inches
Between 0.119 inches and 0.131 inches Maximum Pressure Rating:
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material:
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator:
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular Specification Or Standard:
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular Specification Or Standard: 400 series and 6.000 size
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular Specification Or Standard: 400 series and 6.000 size Shelf Life:
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular Specification Or Standard: 400 series and 6.000 size Shelf Life: N/a
Between 0.119 inches and 0.131 inches Maximum Pressure Rating: 400.0 pounds per square inch Material: Asbestos and steel Style Designator: Circular Specification Or Standard: 400 series and 6.000 size Shelf Life: N/a

Fiig: A032a0